


C211G SERIES SWING ARM TIRE CHANGER


Product Features

1. COSENG designed double-structure cabinets.
2. High quality pressure tubing from Japan.
3. 80mm width swing arm design for more strength mounting and demounting.
4. Adjustable long protection sleeve for vertical hexagonal arm.
5. Adjustable bead breaker shovel (only GC model).

Construction Details



58kg double-structure cabinet




80mm swing arm width design.



Hexagonal long protection sleeve with adjustable bolt



Octagonal precision turn table



200mm Bead Breaker System with 2500kgs of bead breaking force



COSENG proprietary rotating union design



Model	C211GA	C211GB	C211GC
Outside clamping	10"-18"	11"-21"	10"-24"
Inside clamping	12"-20"	13"-23"	12"-26"
Max wheel width	12"	13"	14"
Max wheel diameter	39"	39"	42"
Working air pressure	8bar	8bar	8bar
Shipping weight	225kg	235kg	265kg
Voltage options	110V/50HZ/60HZ 1PH 220V/50HZ/60HZ 1PH 380V/50HZ/60HZ 3PH	110V/50HZ/60HZ 1PH 220V/50HZ/60HZ 1PH 380V/50HZ/60HZ 3PH	110V/50HZ/60HZ 1PH 220V/50HZ/60HZ 1PH 380V/50HZ/60HZ 3PH
Packing size	97*77*100cm	97*77*100cm	115*77*100cm
Other			Adjustable shovel

Standard Accessories:



LPJP



BBSPP



TLPP



MHPP



STL



DVD and manual



4 IN 1 IG

Optional Accessories :



DAAL



211GDAS




HDTL



SPJP



NHMC



PMH (SA)



REPP