

Monty® 3300-24 2-Speed GP Plus



TYRE CHANGER

Tilt back post tyre changer with 2 speeds and 24" clamping capability

- Certified by wdk
- With pneumatic mounting tool easymont pro and plus kit for handling of UHP and run-flat tyre systems (additional optional adaptors required for PAX and CSR tyres)
- Double-acting bead breaker cylinder
- Mounting head pneumatically adjusted in spaced-apart position relative to the rim
- Self-centring four-jaw chuck
- Plastic protection inside jaws and on mounting head
- Pedal-operated post, pneumatically tilted backwards and forwards
- Post pneumatically locked in working position
- Two-speed inverter technology to optimise speed and torque depending on the requirements of the mounting and demounting operations
- Pedal-operated inflation and quick-inflating valve
- Bead breaker blade supported in three joints
- Tool box with integrated precision pressure gauge
- Includes top-side bead seating kit

Technical data and dimensions		
Inner clamping range	inch	12–24
Outer clamping range	inch	10–24
Rim width	inch	3–12
Max. tyre width	inch	12
Max. wheel diameter	mm	1000
Bead breaking range	mm	50–430
Dimensions (W x D x H)	mm	1230 x 1340 x 1610
Weight	kg	300
Compressed air supply	bar	8–12
Power supply		230 V 1ph 50–60 Hz