

TEL05006

Two Stage Transmission Jack with Upgraded Seal Kit 0.5 Ton



SPECIFICATIONS

Capacity: 500KG

Minimum Height: 875mm

Maximum Height: 1855mm

Net Weight: 76KG

Gross Weight: 85KG

Freight Dimensions:

L 850mm W 581mm H 360mm W 87KG

FEATURES

- » Durable frame is constructed of high-grade steel and built to exacting standards for quality and durability
- » Lead-free paint finish is applied after a thorough chemical wash to ensure a long-lasting finish and to help prevent rust
- » Paint is oil, grease and dirt-resistant for easy cleanup
- » High quality large diameter hydraulic steel cylinder unit results in lower oil pressure needed to move the load, which helps to reduce wear and extend service life
- » Piston-ram is treated and polished to resist skiving
- » Piston-ram utilizes a Y-Style polyurethane sealing ring with backup ring, preventing load from falling slowly or bypassing oil drift
- » Hydraulics are powered with a high quality oil, which offers better corrosion resistance and high/low temperature flexibility, allowing the unit to operate at temperatures between 40 degrees F and 105 degrees F
- » Wide base provides exceptional stability
- » Saddle has forward tilt of 14°, aft tilt of 72°, right 31° and left 45°, and features adjustment knobs for controlling tilt
- » Raises and lowers easily using pump handle with comfortable rubberized grip