

COMBO 3 - C233GCIT-NAAR + SP733N

C201GB Tyre Changer with Pneumatic Assist Arm & SP733N Wheel Balancer

C233GCIT-NAAR

Tyre Changer with Pneumatic Assist Arm



Power Requirements: 240v - 10 amps - 10 amp plug

Working Air Pressure: Requires 8 bar

Freight Dimensions: 77 x 110 x 115cm 290kg
115 x 52 x 30cm 100kg

- » Double-structure cabinets
- » 2500 kgf bead breaker cylinder
- » Tilt Back column design
- » Pneumatic horizontal and vertical arm locking system
- » Adjustable bead breaker shovel
- » Includes toolbox and air gauge
- » Hose with heavy duty flow through chuck
- » Air tank
- » Table top inflation system plus internal air connections including bead blaster air inflation control pedal system
- » NAAR - Right side pneumatic assist arm features
- » Powerful pneumatic controlled assist arms

SP733N

Magnetic Levitation Wheel Balancer



Power requirements: 240v - 3amps - 10 amp plug

Freight Dimensions: 97 x 77 x 115cm 146kg

- » Magnetic levitation system (MLS) and self propelled balancing (SPBU)
- » 512 angular positions
- » Smart Position Locator
- » Linear optical encoder
- » Advanced spin brake
- » Quadruple frequency multiplier
- » 8 Balancing modes including normal, static, APS, ALU-S, ALU2, ALU3, ALU4, ALU5
- » Automatic wheel data input
- » Smart user saver
- » 8 modes of balancing
- » LCD Display and Key Pad